

11B Series – Specifications

Case – Machined from solid extruded brass.
 Standard finish is 626 satin chromium plated.
 Width – 1 5/8"
 Length – 2 1/16"
 Thickness – 25/32"

Shackle – The shackle locks at both heel and toe.
 The length of shackle opening is measured from top of case to inside of shackle when padlock is locked.

Material – Brass or stainless steel

Diameter – 1/4"

Width of opening – 7/8"

ASTM F883 – Meets Grade 3 with stainless steel shackle.

ASTM F883 – Meets Grade 6 for option E. (Corrosion resistance).



11B Padlock



11B72

11B722

11B772

11B782

11B – How to Order

11B	7	2	T	626		
Series	Core Housing	Shackle Height	Function Code	Chain Option	Special Stamp No.	Options
11B – brass 1/4" diameter	7 – 7 pin housing accepts all BEST® cores	Steel 2 – 3/4" 22 – 1 1/2" 72 – 2" 82 – 4" Brass 0 – 3/4" 20 – 1 1/2" 70 – 2" 80 – 4"	T – key retained L – non-key retained	M – case drilled for clevis only M1* – bronze chain (available for brass padlocks only) M5* – galvanized steel chain	Blank – BEST® logo PS1010 – safety first Specify padlock stamp number or describe stamp. Price for special stamps on request.	F3 – frangible shackle (11B720 only) 606 – satin brass ZZ – double lockout
				page 8	page 8	page 8