BFII SERIES – 120 MINUTE FIRE

U.L. LISTED LEVEL II BURGLARY



SECURITY

- 1/2" solid steel plate door
- 21/4"-Thick Body with 1/8" outer shell and 5/16" thick inner liner
- Combined steel thickness of 1/2" in body construction
- UL Level II RSC Burglary Classification (2-Man team, 10-minute test. Utilizes same tools as a TL-15)
- AMSEC's patented active hardplate
- TL-15 boltwork with 10 massive 11/2" Chrome Plated Bolts
- 4 Pre-Cut Anchor Holes

WARRANTY

- 5-year parts and labor warranty when purchased with a factory installed AMSEC lock.
- Special lifetime warranty for damage from burglary attempts and fire.

BFII SERIES CONSTRUCTION



BFII GUN SAFES: 11GA OUTER STEEL LINER WITH A COMBINED 5/16" INNER STEEL LINER PROVIDING A TOTAL 1/2" THICK STEEL BARRIER FOR ADDED BURGLARY PROTECTION









FIRE PROTECTION

- Seamless DryLight Fill
- 120-Minute Intertek Verified Fire Rating
- Dual Door Seals to Protect Against Fire and Smoke

FUNCTIONALITY

- Industry's Most Flexible Interior
- Door Organizer
- Storage for Long Guns or Assault Rifles on Door
- Mirrored Back for Added Interior Visibility
- AC Power Outlet with Removable Cord

REIL SPECIFICATIONS

BEIL OF ECHICATIONS			
Model	Outside Dim H x W x D	Interior Capacity	Weight Lbs.
BFII7250	71-1/4 "x 50" x 28"	14-14-14-28-42 + 2 Gun 73 + 2 Gun	2,438
BFII7240	71-1/4" x 40" x 26"	12-12-12-24-36 + 2 Gun 58 + 2 Gun	1,991
BFII6636	65-1/4" x 36" x 26"	12-12-24 + 2 Gun	1,716
BFII6030	59-1/4" x 30" x 26"	11-11-22 + 2 Gun	1,395
BFII6032	59-1/4" x 30" x 21"	9-9-18 + 2 Gun	1,244
BFII6024	59-1/4" x 24" x 21"	8-8-16 Gun + 1 Gun	1,067