

SARGENT AND GREENLEAF®

A Subsidiary of Stanley Security Solutions, Inc.

The Brute® Electronic Door Deadlatch



National Stock Numbers 5340-01-020-5681 and 6350-00-610-1962 can refer to any model of The Brute® deadlatch. You must specify inswing or outswing and strike number. This is the only way to ensure you receive hardware suited to your application.

Electrical Specifications:

Required voltage: 24 VDC

DC coil resistance: 6 OHMS

Current: 5.5 to 6.5 AMPS

Minimum recommended wire size: 18 gauge

- Surface mounted for ease of installation and suitability for a wide range of applications.
- Inside release knob provides for rapid egress.
- Strikes available for both inswing and outswing doors.
- An ideal security solution for indoor applications, such as ATM rooms, cash handling areas, research laboratories, etc.
- Originally designed to be used with the (discontinued) S&G® Code/Tronic™ III access control device, The Brute® deadlatch can be used with any control device that meets its electrical requirements.
- The Brute® deadlatch uses a heavy duty 12 VDC solenoid. The 24 VDC voltage requirement increases bolt retraction force and will not harm the solenoid.

The Brute

Order Number	Application	Included Strike(s)
8497-100	inswing door	#1 for inswing doors
8497-101	outswing door	#2 for outswing doors
8497-102	inswing door	#3 for inswing doors
8497-103	outswing door	#9 for outswing double doors
8497-105	inswing door	none
8497-106	outswing door	none

